




RoHS

REV.	DESCRIPTION	DATE
A	ISSUE	Jan/09/2025




- NOTES:
1. ELECTRICAL CHARACTERISTICS:
CURRENT RATING: 4A
TEMPERATURE RANGE: -20°C TO +80°C
DIELECTRIC WITHSTANDING VOLTAGE:
500V AC FOR ONE MINUTE
2. HOW TO ORDER: B12D-S1xxSM
- 03 - 3 PINS
04 - 4 PINS
05 - 5 PINS



B12D-S103SM



B12D-S104SM



B12D-S105SM

PIN ASSIGNMENT FRONT VIEW (前視圖)

※Cable specification and length can be customized.

5	OVERMOLD	PU or PVC.	BLACK	1	98-135
4	RING NUT	Brass, Nickel Plated.		1	
3	METAL SLEEVE	Brass, Nickel Plated.		1	
2	CONTACT	Brass, 6 u" Gold Plated. Male Contact.		N	
1	CONNECTOR	M12 B-Coding Male Connector Insert. Nylon+GF.	BLACK	1	
No.	PART NAME	DESCRIPTION	COLOR	Q'TY	REMARKS

HOLIN® HTP ASIA TECHNOLOGY CO., LTD. 禾凌科技股份有限公司					
UNIT: mm		TITLE : M12 B-Coding Male Shielded Molded Cable			
SCALE		1:1		P/N: B12D-S1xxSM	
UNLESS OTHERWISE SPECIFIED TOLERANCES:		XX. ± 1.0 .X ± 1.0 .XX ± 0.5 .XXX ± 0.25 ANGLE ± 1°		DR. SIBYL	
REV. A		SHEET 1/1		CH. JAMES	
DWG.NO: B12D-S1xxSM				AP.	