



RoHS



REV.	DESCRIPTION	DATE
A	ISSUE	Feb/11/2025



NOTES:

1. ELECTRICAL CHARACTERISTICS:

CURRENT RATING: 2A/4A

TEMPERATURE RANGE: -20°C TO +80°C

DIELECTRIC WITHSTANDING VOLTAGE:

500V AC FOR ONE MINUTE

2. HOW TO ORDER: C12x-S1xxRM

03 - 3 PINS


04 - 4 PINS

05 - 5 PINS

06 - 6 PINS

N - CURRENT RATING 2A

D - CURRENT RATING 4A



C12D-S103RM C12D-S104RM C12N-S105RM C12N-S106RM

PIN ASSIGNMENT FRONT VIEW (前視圖)

※Cable specification and length can be customized.

5	OVERMOLD	PU or PVC.	BLACK	1	309-135
4	RING NUT	Brass, Nickel Plated.		1	
3	METAL SLEEVE	Brass, Nickel Plated.		1	
2	CONTACT	Brass, 6 u" Gold Plated. Male Contact.		N	
1	CONNECTOR	M12 C-Coding Male Connector Insert. Nylon+GF.	BLACK	1	
No.	PART NAME	DESCRIPTION	COLOR	Q'TY	REMARKS

HOLIN® HTP ASIA TECHNOLOGY CO., LTD.
禾凌科技股份有限公司

	UNIT: mm	TITLE : M12 C-Coding Male Shielded R/A Molded Cable		
SCALE	1:1			
UNLESS OTHERWISE SPECIFIED TOLERANCES: XX, ±1.0 .X ±1.0 .XX ±0.5 .XXX ±0.25 ANGLE ± 1°		P/N: C12x-S1xxRM		DR. SIBYL
REV. A		SHEET 1/1		CH. JAMES
		DWG.NO: C12x-S1xxRM		AP.