





Recommended
Panel Cut-Out


RoHS



REV.	DESCRIPTION	DATE
A	ISSUE	Aug/12/2024



- NOTES:
- ELECTRICAL CHARACTERISTICS:
CURRENT RATING: 12A
VOLTAGE RATING : 630V
TEMPERATURE RANGE: -25°C TO +85°C
DIELECTRIC WITHSTANDING VOLTAGE:
500V AC FOR ONE MINUTE
 - PANEL THICKNESS MAX. 3.0mm
 - HOW TO ORDER: S12P-M1xxHSR
03 - 2 PINS + PE
04 - 3 PINS + PE



S12P-M103HSR S12P-M104HSR

PIN ASSIGNMENT FRONT VIEW (前視圖)

7	GLUE	Epoxy.	BLACK	1	
6	HEX NUT	BRASS, Nickel Plated.		1	
5	GASKET	EPDM.	BLACK	1	
4	METAL BODY	BRASS, Nickel Plated.		1	
3	CONTACT	BRASS , 6 u" Gold Plated . Male Contact.		1	
2	CONTACT	BRASS , 6 u" Gold Plated . Male Contact.		N	
1	CONNECTOR	M12 S-Coding Male Connector Insert.NYLON+GF.	BLACK	1	
No.	PART NAME	DESCRIPTION	COLOR	Q'TY	REMARKS

HOLIN® HTP ASIA TECHNOLOGY CO., LTD. 禾凌科技股份有限公司				
	UNIT: mm	TITLE M12 S-Coding Male Panel Connector Rear Mount Hex Flange With Solder Bucket Pin		
SCALE	1.5:1			
UNLESS OTHERWISE SPECIFIED TOLERANCES: XX. ± 0.5 .X ± 0.5 .XX ± 0.25 .XXX ± 0.1 ANGLE ± 1°		P/N: S12P-M1xxHSR	DR. James	
			CH. Eric	
REV. A	SHEET 1/1	DWG.NO: S12P-M1xxHSR	AP.	